



Terminal of Compression

Catalog ID: 01B1C9R

Terminal of Compression is one kind of connectors used on overhead line construction and pole line installations.

All the package, color is customized by our clients.

It is made of Aluminum. Aluminum has lower density than other metals.

It forms a protective layer of oxide to protect the terminal when it exposes to the air.



PRODUCT DETAILS

General

Material	Aluminum
Material – Body	Aluminum
Number of Pad Holes	2
Physical Attribute – Number of Holes	2
Style	Impact Extruded

Dimensions

Diameter – Pad Bolt	0.5 in (12.7 mm)
Dimension – Hole Size inch	0.500 in (12.7 mm)
Weight	0.882 lb (0.4 kg)

Conductor Related

Conductor Compatibility	ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Chickadee-397.5-18/1;ACSR-Brant-397.5-24/7;ACSR-Ibis-397.5-26/7;ACSR-Lark-397.5-30/7;ACSR-Pelican-477-18/1;ACSR-Flicker-477-24/7;ACSR-Hawk-477-26/7;ACSR-Hen-477-30/7;ACSR-Osprey-556.5-18/1;ACSR-Parakeet-556.5-24/7;ACSR-Dove-556.5-26/7;ACSR-Eagle-556.5-30/7;ACSR-Peacock-605-24/7;ACSR-Squab-605-26/7;ACSR-Kingbird-636-18/1;ACSR-Swift-636-36/1;ACSR-Brahma-203.2-16/19;AAC-Tulip-336.1-19;AAC-Daffodil-350-19;AAC-Canna-397.5-19;AAC-Cosmos-477-19;AAC-Syringa-477-37;AAC-Zinnia-500-19;AAC-Hyacinth-500-37;AAC-Dahlia-556.5-19;AAC-Mistletoe-556.5-37;AAC-Meadowsweet-600-37;AAC-Orchid-636-37;AAC-Flag-700-61;AAC-Cattail-750-61;ACAR-653.1-12/7
Conductor Diameter (VersaCrimp) – Maximum	0.966 in (24.54 mm)
Conductor Diameter (VersaCrimp) – Minimum	0.659 in (16.74 mm)

Logistics

Carton Quantity	40
-----------------	----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>