



Terminal with Bolts, Pad width 3 in

Catalog ID: 01B1D9W

Terminal
With 90° pad orientation and 45° pad orientation



PRODUCT DETAILS

General

EU RoHS Indicator	No
Material	Aluminum
Material – Clamping Hardware	Aluminum Alloy
Number of Bolt Holes	4
Number of Pad Holes	4
Type	Bolted Lugs & Terminals

Dimensions

Angle – Pad	180 °
Width – Pad	3 in (76.2 mm)

Conductor Related

Conductor Compatibility	ACSR-Finch-1113-54/19;ACSR-Bunting-1192.5-45/7;ACSR-Grackle-1192.5-54/19;ACSR-Bittern-1272-45/7;ACSR-Pheasant-1272-54/19;ACSR-Dipper-1351.5-45/7;ACSR-Martin-1351.5-54/19;ACSR-Bobolink-1431-45/7;AAC-Narcissus-1272-61;AAC-Columbine-1351.5-61;AAC-Carnation-1431-61;AAC-Gladiolus-1510.5-61;AAC-Coreopsis-1590-61
Conductor Diameter – Maximum	1.459 in (37.06 mm)
Conductor Diameter – Minimum	1.289 in (32.04 mm)
Conductor Diameter Range	1.289 in – 1.459 in
Conductor Type	AAC ACSR

Logistics

Pallet Quantity	324
-----------------	-----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
----------------	------------------------------

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>