



## Thimbleye Eyenut

**Catalog ID: 03G4K9K**

Thimbleye Eyenuts are fasteners used for power line hardware systems. It is applied for Pisa Anchor Rods for power and utility requirements. Ultimate strength ratings apply to properly installed anchors only. Hot dipped galvanized per ASTM A153



### PRODUCT DETAILS

#### General

Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Eyenut Style	Thimbleye
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	16000 lb
Type	Power Installed Screw Anchor (PISA)

#### Dimensions

Rod Diameter	0.625 in (15.88 mm)
Weight	0.853 lb (0.39 kg)

#### Certifications and Compliance

RUS Listed Reference	z – Anchors, screw, power installed
----------------------	-------------------------------------

#### Logistics

Pallet Quantity	1600
Standard Package	25

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>