



Automatic Splice

Catalog ID: 01C5L9Z

Automatic Splice—overhead line connector

Copper; Gripping Unit: Bronze Alloy

Automatic Splice mechanically secure wires and form an electrical connection for power transmission.



PRODUCT DETAILS

General

| | |
|--------------------------|--------------|
| Material | Copper |
| Material – Gripping Unit | Bronze Alloy |

Dimensions

| | |
|--------|--------------------|
| Weight | 0.137 lb (0.06 kg) |
|--------|--------------------|

Conductor Related

| | |
|------------------------------|------------|
| Conductor Diameter – Maximum | 0.2 |
| Conductor Diameter – Minimum | 0.16 |
| Conductor Diameter Range | 0.16 – 0.2 |

Logistics

| | |
|-----------------|-------|
| Pallet Quantity | 15000 |
|-----------------|-------|

RESOURCES AND DOWNLOADS

| | |
|--------------------|------------------------------|
| Specifications | Download PDF |
| Technical Drawings | Download PDF |

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com
Website: <https://ttfpower.com>