



Copper Terminal Compression

Catalog ID: 01B5V7R

Copper Terminal Compression—electrical overhead line connectors. It is used to connect various types of wires and cables to power systems for usage. Bronze; Clamping Hardware: Stainless Steel
Terminal / Lug, Bolted
Two holes for stability



PRODUCT DETAILS

General

Material	Bronze
Material – Clamping Hardware	Stainless Steel
Number of Pad Holes	2
Type	Terminal / Lug, Bolted

Dimensions

Angle – Pad	180 °
Weight	1.960 lb (0.89 kg)
Width – Pad	1.63 in (41.4 mm)

Conductor Related

Conductor Diameter – Maximum	0.681 in (17.3 mm)
Conductor Diameter – Minimum	0.258 in (6.55 mm)
Conductor Diameter Range	0.258 – 0.681
Conductor Type	Copper

Logistics

Pallet Quantity	1008
-----------------	------

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>