



## Deadend for Distribution Feeder

**Catalog ID: 01A7L1Z**

Deadend for Distribution Feeder—overhead line connectors  
 It is applied in Primary, Secondary and Substation Feeders.  
 It is designed to meet your power and utility needs.  
 Overhead Formed Wire  
 Aluminum Clad Steel  
 High holding strength



### PRODUCT DETAILS

#### General

Application	Deadend for Distribution Feeder
Color Code	Black
Material	Aluminum Clad Steel
Product Category	Overhead
Type	Formed Wire

#### Dimensions

Length	35 in (889 mm)
Weight	1.273 lb (0.58 kg)

#### Conductor Related

Conductor Diameter – Maximum	0.653
Conductor Diameter – Minimum	0.578
Conductor Diameter Range	0.578 – 0.653
Conductor Type	ACSR, AAC, AAAC, Compacted ACSR and so on

#### Logistics

Pallet Quantity	700
-----------------	-----

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>