



## Distribution Arrester Transformer Bracket

Catalog ID: 08A9X4T

Distribution Arrester Transformer Bracket

Silicone Polymer Housing with vertical and perpendicular mounting position  
It aims to prevent power cords grounds faults and shorts caused by lighting or switching overvoltages.

Protect nearby animal and passersby



### PRODUCT DETAILS

#### General

Application	Distribution
Bracket Type	Transformer Bracket
Cantilever Bending Strength – Max.	80 Nm
Color	Gray Housing
Material	Silicone Polymer Housing
Mounting Position	Upright
Type	Distribution

#### Dimensions

<b>Height</b>	<b>5.5 in (139.7 mm)</b>
Stud Type	3/8-16

#### Electrical Ratings

<b>Creep and Leakage Distance</b>	<b>17 in (431 mm)</b>
Current – Low Current Long Duration (LCLD) Test	250 A
Duty Cycle	12 kV
Frequency Rating	48-62 Hz
MCOV	10.2 kV
Maximum .5 Microsecond Discharge Volts @ Classifying Current	42.1 kV
Maximum Discharge Voltage	30.4 kV @ 1.5 kA 32.6 kV @ 3 kA 34.5 kV @ 5 kA 37.6 kV @ 10 kA 42.7 kV @ 20 kA 50.3 kV @ 40 kA
Maximum Switching Surge Protective Level @ 500A	27.8 kV
Minimum Strike	6.6 in

<b>Creep and Leakage Distance</b>	<b>17 in (431 mm)</b>
Pressure Relief Capability-Symmetrical rms (kA)	20
Time – Low Current Long Duration (LCLD) Test	2000 $\mu$ s

#### **Certifications and Compliance**

Industry Standard(s)	IEEE/IEC
----------------------	----------

#### **RESOURCES AND DOWNLOADS**

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

#### **TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>