



## Distribution Arrester with Bracket

**Catalog ID: 08A2P4E**

Distribution Arrester—electrical power hardware  
 Power surge arrester set with bracket  
 Over-voltage insurance an electric framework from exorbitant voltage  
 Can be installed at home or on distribution line  
 Polymer Housing material



### PRODUCT DETAILS

#### General

Application	Distribution
Bracket Type	NEMA Crossarm Bracket
Color	Gray
Material	Polymer Housing

#### Dimensions

Stud Type	M12
-----------	-----

#### Electrical Ratings

Creep and Leakage Distance	25.5 in (648 mm)
Current – Low Current Long Duration (LCLD) Test	75A
Duty Cycle	15 kV
Frequency Rating	48-62 Hz
MCOV	12.7 kV
Maximum .5 Microsecond Discharge Volts @ Classifying Current	50.6 kV
Maximum Discharge Voltage	39.9 kV @ 1.5 kA 42.5 kV @ 3 kA 45.3 kV @ 5 kA 51 kV @ 10 kA 58.9 kV @ 20 kA 73.7 kV @ 40 kA
Maximum Switching Surge Protective Level @ 500A	35.7 kV
Pressure Relief Capability-Symmetrical rms (kA)	15
Time – Low Current Long Duration (LCLD) Test	2000 microsec
Withstand Voltage – 60 Hz Wet	49.4
Withstand Voltage – Lightning Impulse	88.6

## RESOURCES AND DOWNLOADS

---

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

---

*For further technical assistance, please contact us*

### **TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>