



## Ground Wire Suspension Clamp

**Catalog ID: 05G8T8N**

Ground Wire Suspension Clamp used as ground wires with galvanized steel cable. Different parts are made by different materials. Clamps are made by galvanized ductile iron. The Material of Hardware is galvanized steel. The diameter of clevis bolt is the same as clevis pin.



### PRODUCT DETAILS

#### General

Bolt Installation Torque (Recommended)	480 in-lbs
Fitting Type	None
Material – Clamp	Ductile Iron
Material – Hardware	Galvanized Steel
Material – Pin	Stainless Steel
Material – Pin (Cotter)	Stainless Steel
Product Category	Suspension Clamp
Strength Rating – Ultimate Body	16000 lb (7257.48 kg)
Type	Ground Wire Suspension Clamps
U-Bolts	1/2 in (12.7 mm)

#### Dimensions

Angle – Take-Off Maximum	30 °
Clamping – Maximum	0.6 in (15.24 mm)
Clamping – Minimum	0.2 in (5.08 mm)
Clevis Opening	0.875 in (22.23 mm)
Diameter – Clevis Pin	0.625 in (15.88 mm)
Height	2.0 in (50.8 mm)
Length	6.4375 in (163.51 mm)
Weight	2.7 lb (1.22 kg)

#### Conductor Related

Clamping Range	0.2 in- 0.6 in
----------------	----------------

#### Logestic

---

**RESOURCES AND DOWNLOADS**

---

Specifications

[Download PDF](#)

Technical Drawings

[Download PDF](#)

---

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)Website: <https://ttfpower.com>