



Spring Loaded Straight line Deadend

Catalog ID: 05B8F6B

Spring Loaded Straight line Deadend—overhead line connector
It is designed to secure the completeness of conductors as well as protect other electrical line fittings.
Aluminum Alloy; Steel
For anti-corrosion nature



PRODUCT DETAILS

General

Material	Aluminum Alloy; Steel
Material – Body	356 T6 Aluminum Alloy
Material – Bolt	Galvanized Steel
Material – Hardware	Galvanized Steel
Material – Keeper	356 T6 Aluminum Alloy
Product Category	Straight Line
Strength Rating – Ultimate Body	8000 lb
Style	ASOD
Type	Bolted
U-Bolts	1

Dimensions

Diameter – Bolt	0.5 in (12.7 mm)
Diameter – Pin	0.625 in (15.88 mm)
Weight	1.990 lb (0.9 kg)

Conductor Related

Conductor Diameter – Maximum	0.69
Conductor Diameter – Minimum	0.25
Conductor Diameter Range	0.25 – 0.69

Logistics

Pallet Quantity	600
-----------------	-----

RESOURCES AND DOWNLOADS

Specifications

Download PDF

Technical Drawings

Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>