



Upright Distribution Arrester

Catalog ID: 08A4W0M

Upright Distribution Arrester
 Silicone Polymer Housing with vertical and perpendicular mounting position
 Normal duty
 Color: Gray
 Mounting Hardware: Insulating Bracket with Disconnecter
 Manufactured in compliance with IEEE/IEC Industry Standard



PRODUCT DETAILS

General

Application	Distribution
Bracket Type	NEMA 4×5 Crossarm Bracket
Cantilever Bending Strength – Max.	45 Nm
Color	Gray
EU RoHS Indicator	Contact Manufacturer
Material	Silicone Polymer Housing
Mounting Hardware	Insulating Bracket with Disconnecter
Mounting Position	Upright
Type	Distribution

Dimensions

Height	14.7 in (373.38 mm)
Maximum Operating Altitude	12000 ft

Electrical Ratings

Creep and Leakage Distance	30.8 in (782 mm)
Current – Low Current Long Duration (LCLD) Test	75 A
Duty Cycle	24 kV
Frequency Rating	48-62 Hz
MCOV	19.5 kV
Maximum .5 Microsecond Discharge Volts @ Classifying Current	79.7 kV

Creep and Leakage Distance	30.8 in (782 mm)
Maximum Discharge Voltage	62.9 kV @ 1.5 kA 67 kV @ 3 kA 71.4 kV @ 5 kA 80.4 kV @ 10 kA 92.2 kV @ 20 kA 116.2 kV @ 40 kA
Maximum Switching Surge Protective Level @ 500A	56.3 kV
Minimum Strike	11.5 in (292.1 mm)
Pressure Relief Capability-Symmetrical rms (kA)	15
Time – Low Current Long Duration (LCLD) Test	2000 μ s

Certifications and Compliance

Industry Standard(s)	IEEE/IEC
----------------------	----------

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>