



CATALOG NUMBER : 01A2K3N

ITEM	DESCRIPTION	MATERIAL
1	FORMED WIRE DEADENDS	GALVANIZED STEEL
1	FORMED WIRE DEADENDS	BEZINAL STEEL

GALV. STEEL CAT.NO.	BEZINAL STEEL CAT.NO.	APPLICATION RANGE	STRAND SIZE & CONSTRUCTION	NO.OF WIRES	DIM "A"	DIM "B"	DIM "C"	MAXIMUM RBS	WEIGHT
01A7T3D_1	01A2K3N_1	0.231 - 0.259 [5.86 - 6.57]	1/4 (3W OR 7W)	5	36 [914.4]	19 [482.6]	1.000 [25.40]	6650 [29.6]	.600 [.272]
01A7T3D_2	01A2K3N_2	0.292 - 0.336 [7.41 - 8.53]	5/16 (3W OR 7W)	5	39 [990.6]	21.5 [546]	1.250 [31.75]	11200 [49.8]	.921 [.418]
01A7T3D_3	01A2K3N_3	0.337 - 0.394 [8.56 - 10.00]	3/8 (3W OR 7W)	6	42 [4066.8]	24 [609.6]	1.250 [31.75]	15400 [68.5]	1.151 [.522]
01A7T3D_4	01A2K3N_4	0.395 - 0.474 [10.03 - 12.04]	7/16 (7W)	6	48 [1219.2]	31 [787.4]	1.250 [31.75]	20800 [92.5]	1.966 [.892]



NOTES:

1. ALL DIMENSIONS FOR REFERENCE ONLY. DISTANCE, [MM], FORCE LBS, [KN], TORQUE IN. LBS, [N.M], & WEIGHT LBS, [KG].
2. RATINGS:
 - A. ALL DEAD-ENDS MEET 100% OF THE WIRE RATED BREAKING STRENGTH (RBS) AS SHOWN IN TABLE
 - B. ALL DEAD-ENDS PASSED 5% ACIDITY SALT FOG TESTING PER ASTM B117
3. CERTIFICATIONS, SPECIFICATIONS, & STANDARDS:
 - A. GALV. WIRE - CARBON STEEL, ZINC-PLATED CLASS "B" COATING ASTM A64.
 - B. BEZINAL WIRE - CARBON STEEL, 95% ZINC & 5% ALUMINUM PLATED ASTM A855.
4. SUFFIXES & VARIANT CONFIGURATION
 - A. N/A
5. HAND LAY DIRECTION: LEFT

DRN BY:	DATA
Ella	10/10/16

GUY WIRE FALSE DEADEND

CONFIDENTIAL. THIS DRAWING AND ITS CONTENTS PROPERTY OF TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO., LTD. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO., LTD. TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO., LTD. UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.



TTF POWER TECHNOLOGY CO.