



## 4R Stockbridge Damper

**Catalog ID: 05F8F7I**

4R Stockbridge Damper effectively inhibit the wind-induced aeolian vibration from causing conductor and static wire damage.

Application on standard voltage or EHV

Clamping Range 1.94 in – 2.56 in

Bent bolt diameter is 0.75 in

Clevis eye width is 1 in

Hole diameter 0.688 in



### PRODUCT DETAILS

#### General

Bolt Installation Torque (Recommended)	40 ft-lbs
Material – Clamp	Aluminum
Material – Hardware	Aluminum
Style	4R Stockbridge Damper

#### Dimensions

Clamping – Maximum	2.56 in (65.02 mm)
Clamping – Minimum	1.94 in (49.28 mm)
Diameter – Bolt	0.5 in (12.7 mm)
Weight	22.5 lb (10.21 kg)

#### Logistics

Pallet Quantity	48
-----------------	----

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>