



## Aluminum Bolted Cable Spacer

**Catalog ID: 05A9X7Z**

Bolted Cable Spacer—overhead line connectors

It is used for connecting conductors and insulators and other electrical construction components.

Spacing 8 in

Diameter range 1.382 in-1.632 in for AAC, ACSR

Material of body is galvanized ductile iron

Cotter Pin is made by stainless steel

Installation with ANSI class 52-3 insulators



### PRODUCT DETAILS

#### General

EU RoHS Indicator	No
Material	Ductile Iron
Material – Pin (Cotter)	Stainless Steel
Number of Bolt Holes	0
Strength Rating – Ultimate	30000 lb (13607.77 kg)

#### Dimensions

Diameter – Eye Hole	0.813 in (4.65 mm)
Length – Coupling	2.063 in (52.4 mm)
Weight	1.96 lb (0.89 kg)
Width – Eye	2.125 in (53.98 mm)

#### Logistics

Pallet Quantity	1120
-----------------	------

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>