



Aluminum Compression Splice

Catalog ID: 01C5U8D

Aluminum Compression Splice is one kind of connectors used on overhead line construction and pole line installations.

It is a super durable or impermanent association on AAC, ACSR conductors. It is made of Aluminum Alloy against corrosion.



PRODUCT DETAILS

General

Compression Method	VersaCrimp Tooling ONLY
Material	Aluminum Alloy

Dimensions

Length Before Compression	6 in (152.4 mm)
Weight	0.490 lb (0.22 kg)

Conductor Related

ACSR-Pelican-477-18/1;ACSR-Flicker-477-24/7;ACSR-Hawk-477-26/7;ACSR-Hen-477-30/7;ACSR-Osprey-556.5-18/1;ACSR-Parakeet-556.5-24/7;ACSR-Dove-556.5-26/7;ACSR-Eagle-556.5-30/7;ACSR-Peacock-605-24/7;ACSR-Squab-605-26/7;ACSR-Teal-605-30/19;ACSR-Kingbird-636-18/1;ACSR-Swift-636-36/1;ACSR-Rook-636-24/7;ACSR-Grosbeak-636-26/7;AAC-Zinnia-500-19;AAC-Hyacinth-500-37;AAC-Dahlia-556.5-19;AAC-Mistletoe-556.5-37;AAC-Meadowsweet-600-37;AAC-Orchid-636-37;AAC-Flag-700-61;AAC-Violet-715.5-37;AAC-Nasturtium-715.5-61;AAC-Cattail-750-61;ACAR-653.1-12/7;ACAR-739.8-18/19

Conductor Compatibility

Conductor Diameter (VersaCrimp) – Maximum	0.998 in (25.35 mm)
Conductor Diameter (VersaCrimp) – Minimum	0.811 in (20.6 mm)

Logistics

Carton Quantity	80
-----------------	----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
----------------	------------------------------

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>