



Aluminum Compression Terminal

Catalog ID: 01B3B5D

Aluminum Compression Terminal is one kind of connectors used on overhead line construction and pole line installations.

All the package, color is customized by our clients.

It is made of Aluminum. Aluminum has lower density than other metals.

It forms a protective layer of oxide to protect the terminal when it exposes to the air.



PRODUCT DETAILS

General

Material	Aluminum Alloy – Tin Plated
Material – Body	Aluminum
Number of Pad Holes	1
Physical Attribute – Number of Holes	1
Style	Pressed Tubing

Dimensions

Diameter – Pad Bolt	0.38 in (9.65 mm)
Dimension – Bolt Hole Size inch	0.380 in (9.65 mm)
Weight	0.020 lb (0.01 kg)

Conductor Related

Conductor Compatibility	AAC-Iris-2-7
Conductor Diameter (VersaCrimp) – Maximum	0.292 in (7.42 mm)
Conductor Diameter (VersaCrimp) – Minimum	0.292 in (7.42 mm)

Certifications and Compliance

UL Listed	Yes
-----------	-----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>