



Aluminum Straight line Deadend

Catalog ID: 05B7Z3P

Straight line Deadend—overhead line connector with non-fittings
 It is designed to secure the completeness of conductors as well as protect other electrical line fittings.
 Conductor Compatibility ACSR;AAC;AAAC;ACAR



PRODUCT DETAILS

General

Fitting Type	None
Material	Aluminum
Material – Body	356 T6 Aluminum Alloy
Material – Hardware	Galvanized Steel
Material – Keeper	356 T6 Aluminum Alloy
Product Category	Straight Line
Strength Rating – Ultimate Body	15000 lb (6803.89 kg)
Type	Bolted
U-Bolts	2 in

Dimensions

Diameter – Bolt	0.5 in (12.7 mm)
Diameter – Pin	0.625 in (15.88 mm)
Weight	2.52 lb (1.14 kg)

Conductor Related

Conductor Diameter – Maximum	0.88 (22.35 mm)
Conductor Diameter – Minimum	0.31 (7.87 mm)
Conductor Diameter Range	0.31 in – 0.88 in

Logistics

Pallet Quantity	480
-----------------	-----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>