



Aluminum Suspension Clamp

Catalog ID: 05A5I3U

Aluminum Suspension Clamp—overhead line connectors
 It can provide better support and protection for conductors.
 The wire is directly attached to the helical rods to hold the rubber inserts in place.
 Material if clamp body & strap is aluminum alloy.
 Rubber Insert is made by EPDM Rubber
 Clamping Range is 0.284 in -0.294 in



PRODUCT DETAILS

General

EU RoHS Indicator	No
Material	Stainless Steel
Number of Bolt Holes	0
Strength Rating – Ultimate Body	0 lb

Dimensions

Insulator Throat Diameter Range	0 – 0
Length – Pin	0 in
Maximum Adjustment	0 in
Ring Height	0 in
Weight	0.01 lb (0.005 kg)

Logistics

Pallet Quantity	7200
-----------------	------

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>