



## Cast Aluminum Weldment Terminal

**Catalog ID: 01B3D2F**

Cast Aluminum Weldment Terminal is one kind of Utility connectors used on overhead line construction.

Aluminum with lower density than other metals.

It forms a protective layer of oxide to protect the terminal when it exposes to the air.

2 Bolt Holes and 2 Pad Holes

Used with AAC and ACSR conductors



### PRODUCT DETAILS

#### General

Material	Aluminum
Number of Bolt Holes	2
Number of Pad Holes	2
Type	Terminal, Aluminum Weldment

#### Dimensions

Angle – Pad	180 °
Weight	0.686 lb (0.31 kg)
Width – Pad	2 in (50.8 mm)

#### Conductor Related

Conductor Compatibility	ACSR-Teal-605-30/19;ACSR-Grosbeak-636-26/7;ACSR-Egret-636-30/19;ACSR-Flamingo-666.6-24/7;ACSR-Gannet-666.6-26/7;AAC-Cattail-750-61;AAC-Arbutus-795-37;AAC-Lilac-795-61
Conductor Diameter – Maximum	1.028 in (26.11 mm)
Conductor Diameter – Minimum	0.99 in (25.15 mm)
Conductor Diameter Range	0.99 – 1.028
Conductor Type	AAC ACSR

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>