



Cast Aluminum Terminal

Catalog ID: 01B2L80



Cast Aluminum Terminal is one kind of connectors used on overhead line construction and pole line installations.

All the package, color is customized by our clients.

It is made of Aluminum. Aluminum has lower density than other metals.

It forms a protective layer of oxide to protect the terminal when it exposes to the air.

Aluminum with 4 pad holes and 4 bolt holes

PRODUCT DETAILS

General

Material	Aluminum
Number of Bolt Holes	4
Number of Pad Holes	4
Type	Cable to Flat

Dimensions

Angle – Pad	180 °
Weight	1.862 lb (0.84 kg)
Width – Pad	4 in (101.6 mm)

Conductor Related

Conductor Compatibility	ACSR-Martin-1351.5-54/19;ACSR-Bobolink-1431-45/7;ACSR-Plover-1431-54/19;ACSR-Nuthatch-1510.5-45/7;ACSR-Parrot-1510.5-54/19;ACSR-Lapwing-1590-45/7;AAC-Coreopsis-1590-61
Conductor Diameter – Maximum	1.506 in (38.25 mm)
Conductor Diameter – Minimum	1.424 in (36.17 mm)
Conductor Diameter Range	1.424 – 1.506
Conductor Type	<p>AAC</p> <p>ACSR</p>

Logistics

Pallet Quantity	540
-----------------	-----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
----------------	--------------

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>