



## Compression Jumper Terminal

Catalog ID: 01B7L2U

Aluminum alloy—overhead line connector  
 Specific use on ACSR and ACSS conductors  
 Aluminum alloy with high specific strength, high processability, predominantly anti-erosion, increased conductivity, and eco-friendly characteristic  
 4 Pad Holes  
 Compression Jumper Terminal



### PRODUCT DETAILS

#### General

Compression Method	Uni-Grip (single die system)
Die Size	16CD
Material & Connection Method	Aluminum Compression
Number of Bolt Holes	0
Number of Pad Holes	4
Number of Tees	0
Product Category	Compression Jumper Terminal

#### Dimensions

<b>Length Before Compression</b>	<b>14.2 in (360.68 mm)</b>
Weight	3.949 lb (1.79 kg)
Width – Pad	3 in (76.2 mm)

#### Electrical Ratings

Voltage Application	EHV; Standard
---------------------	---------------

#### Conductor Related

Conductor Compatibility	ACSR-Bobolink-1431-45/7;ACSR-Plover-1431-54/19;ACSR-Nuthatch-1510.5-45/7;ACSR-Parrot-1510.5-54/19;ACSR-Lapwing-1590-45/7;AAC-Coreopsis-1590-61
-------------------------	--

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>