



Copper Compression Terminal

Catalog ID: 01B1V0R

Copper Compression Terminal is one kind of connectors used on overhead line construction and pole line installations.

All the package, color is customized by our clients.

It is made of Copper with 2 bolt holes and 2 Pad Holes.

Copper with high thermal and electrical conductivity

Bolted Lugs & Terminals



PRODUCT DETAILS

General

Material	Copper
Number of Bolt Holes	2
Number of Pad Holes	2
Type	Bolted Lugs & Terminals

Dimensions

Angle – Pad	180 °
Weight	5.488 lb (2.49 kg)
Width – Pad	2 in (50.8 mm)

Conductor Related

Conductor Diameter – Maximum	1.152 in (29.26 mm)
Conductor Diameter – Minimum	1.152 in (29.26 mm)
Conductor Diameter Range	1.152 – 1.152
Conductor Type	Copper

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>