



Crossarm Insulator Pin with Thread

Catalog ID: 06G4S9B

Insulator pins are utilized to hold crossarm-mounted pin-type insulators.
 Designed with 1-3/8 in internal threads.
 Served with two 5/8 in x 7 in carriage bolts, two square nuts, two curved lock nuts
 and a 5/16 in x 1-1/2 in washer plate.
 Cantilever load rating is 1,500 lb (ANSI/IEEE)



PRODUCT DETAILS

General

Coating	Galvanized, ASTM A-153
Material	Steel
Type	Pins

Dimensions

Distance From Pole	N/A
Length – Threaded Area	3 in (76.2 mm)
Weight	6.1 lb (2,77 kg)

Certifications and Compliance

RUS Listed Reference – Pin	crossarm
----------------------------	----------

Logistics

Pallet Quantity	192
-----------------	-----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384
 Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>