



Double Tongue Compression Deadend

Catalog ID: 05B2A6I

Double Tongue Compression Deadend is a type of overhead line connector. It is designed to secure the completeness of conductors as well as protect other electrical line fittings.
 Conductor compatibility ACSR-Joree-2515-76/19
 Standard or EHV voltage application



PRODUCT DETAILS

General

Bolt Installation Torque (Recommended)	0 ft-lbs
Compression Method	Uni-Grip (single die system)
Die Size	20CD
Material	Aluminum; Steel
Material – Body	Seamless Extruded Aluminum Alloy
Material – Eye	Galvanized Forged Steel
Material – Hardware	Aluminum Alloy
Material – Terminal	Seamless Extruded Aluminum Alloy
Number of Bolt Holes	4
Number of Pad Holes	0
Press Minimum	100
Product Category	Eye
Style	Uni-Grip, Double Tongue, Horizontal Eye
Type	Eye

Dimensions

Diameter – Outside	1.802 in (45.77 mm)
Length Before Compression	28.7 in (728.98 mm)
Width – Pad	4 in (101.6 mm)

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>