



Ductile Iron Aluminum Bolted Cable Spacer

Catalog ID: 05A1F0H

Aluminum Bolted Cable Spacer—overhead line connectors

It is used for connecting conductors and insulators and other electrical construction components.

Spacing 8 in

Diameter range 1.382 in-1.632 in for AAC, ACSR

Material of body is galvanized ductile iron

Cotter Pin is made by stainless steel

Have a 4 in pad terminal with 90° Angle



PRODUCT DETAILS

General

EU RoHS Indicator	No
Material	Ductile Iron
Material – Pin (Cotter)	Stainless Steel
Number of Bolt Holes	0
Strength Rating – Ultimate	30000 lb (1360.77 kg)

Dimensions

Length – Coupling	3 in (76.2 mm)
Weight	1.96 lb (0.89 kg)

Logistics

Pallet Quantity	1200
-----------------	------

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>