



## Ductile Iron Cable Spacer

**Catalog ID: 05A6P1M**

Ductile Iron Cable Spacer—overhead line connectors

It is used for connecting conductors and insulators and other electrical construction components.

Spacing 8 in

Diameter range 1.382 in-1.632 in for AAC, ACSR

Material of Body is galvanized ductile iron

Hardware is made by galvanized steel

Cotter Pin-Stainless steel, Shield nut-Aluminum alloy

Have a 4 in pad terminal with 90° Angle



### PRODUCT DETAILS

#### General

Material	Ductile Iron
Material – Pin (Cotter)	Stainless Steel
Number of Bolt Holes	0
Strength Rating – Ultimate	50000 lb (22679.62 kg)

#### Dimensions

Length – Coupling	2.938 in (74.63 mm)
Weight	5.223 lb (2.37 kg)

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

#### **TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>

