



Galvanized Helical Anchor Lead

Catalog ID: 03C5W2J

Galvanized Helical Anchor Lead—ground anchoring products
 Used in weak soil conditions
 High holding capacities
 The anchor lead section has to be install in the proper depth into the soil to meet the power and utility needs in the power line hardwarfe systems.
 Galvanized, ASTM A-153
 2 Helices



PRODUCT DETAILS

General

Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Number of Helices	2
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	70000 lb
Torque Rating	5500 ft-lbs
Type	Lead Sections

Dimensions

Anchor Helix Diameter(s)	8 in (203.2 mm) – 10 in (254 mm)
Length	36.000 in (914.4 mm)
Weight	37.191 lb (16.87 kg)

Certifications and Compliance

RUS Listed Reference	z – Anchors, Power-installed screw
----------------------	------------------------------------

Logistics

Pallet Quantity	20
Standard Package	1

RESOURCES AND DOWNLOADS

Specifications	Download PDF
----------------	------------------------------

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>