



Heavy Duty Ridge Pin

Catalog ID: 06G0E8D

The ridge pin enables the attachment of a pin-style insulator to a pole. The insulator is screwed into the pole's threads. The ridge pin is fastened to the pole's top with a bolt.



PRODUCT DETAILS

General

Description – End Fitting	Vertical Pin
EU RoHS Indicator	No
Material – Threads	1.375" Lead Threads
Strength Rating – Minimum Ultimate, Longitudinal (L)	2,200 lb (997.9 kg)
Strength Rating – Minimum Ultimate, Transverse (T)	2,200 lb (997.9 kg)
Strength Rating – Minimum Ultimate, Vertical (V)	2,500 lb (1137.98 kg)

Dimensions

Diameter – Rod / Tube	2 in (50.8 mm)
Length	12 in (304.8 mm)
Mounting Bolt Spacing	5 in (127 mm) 6 in (152.4 mm) 8 in (203.2 mm)
Weight	9.8 lb (4.45 kg)

Logistics

Carton Quantity	4
Pallet Quantity	160
Standard Package	1

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>