



Helical Lead Anchor

Catalog ID: 03C0L30

Helical Lead Anchor-ground anchoring products

Used in weak soil conditions

High holding capacities

The anchor lead section has to be install in the proper depth into the soil to meet the power and utility needs in the power line hardwarfe systems.

Galvanized, ASTM A-153

2 Helices



PRODUCT DETAILS

General

| | |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application | Helical Anchoring |
| Coating | Galvanized, ASTM A-153 |
| Number of Helices | 2 |
| Strength Note | Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength. |
| Tensile Strength | 70000 lb |
| Torque Rating | 7000 ft-lbs |
| Type | Lead Sections |

Dimensions

| | |
|--------------------------|-----------------------------------|
| Anchor Helix Diameter(s) | 6 in (152.4 mm) – 8 in (203.2 mm) |
| Length | 36.000 in (914.4 mm) |
| Weight | 36.4 lb (16.51 kg) |

Logistics

| | |
|------------------|---|
| Standard Package | 1 |
|------------------|---|

RESOURCES AND DOWNLOADS

| | |
|--------------------|------------------------------|
| Specifications | Download PDF |
| Technical Drawings | Download PDF |

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>