



## **Horizontal Pin Standoff Bracket**

## Catalog ID: 06K3S0U

Horizontal Pin Standoff Bracket–line construction hardware It is designed to provide additional strength and support to other power line components and parts. Bracket used in pole line installaion and construction.

Made by single phase medium duty fiberglass with 1 in nylon thread. Distance from pole 12 in



## PRODUCT DETAILS

## General

| Description – End Fitting                            | Horizonal Pin       |
|--|---------------------|
| Material – Threads                                   | 1" Nylon Threads    |
| Strength Rating – Minimum Ultimate, Longitudinal (L) | 1800 lb (816.47 kg) |
| Strength Rating – Minimum Ultimate, Transverse (T)   | 1500 lb (680.39 kg) |
| Strength Rating – Minimum Ultimate, Vertical (V)     | 1850 lb (839.15 kg) |
| Dimensions   |                     |
| Diameter – Rod / Tube                                | 1.5 in (38.1 mm)    |
| Distance From Pole                                   | 12 in (304.8 mm)    |
| Length   | 12 in (304.8 mm)    |
| Mounting Bolt Spacing                                | 6 in (152.4 mm)     |
|  | 8 in (203.2 mm)     |
| Weight   | 5.2 lb (2.36 kg)    |
| Logistics  |                     |
| Standard Package                                     | 1                   |
| RESOURCES AND DOWNLOADS                              |                     |
| Specifications                                       | Download PDF        |
| Technical Drawings                                   | Download PDF        |
|  |                     |

For further technical assistance, please contact us

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com Website: https://ttfpower.com