



Hot Line Hold Down Shackle

Catalog ID: 05G8R6Y

Hot Line Hold Down Shackle can be used on distribution and transmission line.

The clevis opening is 1 in.

The clevis pin is 0.625 in.

Ultimate tensile strength is 30,000 lb.

The material of the body is galvanized ductile iron or forged steel.

Clevis bolt and nut is made by galvanized steel.

The material of cotter pin is stainless steel.

Served with clevis bolt, nut and cotter Pin.



PRODUCT DETAILS

General

EU RoHS Indicator	No
Material	Steel
Material – Pin (Clevis)	Galvanized Steel
Material – Pin (Cotter)	Stainless Steel
Number of Bolt Holes	0
Strength Rating – Ultimate	10000 lb

Dimensions

Length – Coupling	5.875 in (149.23 mm)
Weight	1.372 lb (0.62 kg)

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com
Website: <https://ttfpower.com>