



## Insulator Double Top Tie

Catalog ID: 01A3T9L

Insulator Double Top Tie is one kind of connectors used on overhead line construction.

It is manufactured of Aluminum Clad Steel.

It is designed to secure conductors on double-arm construction in the power line hardware systems.

Insulator Throat Neck Type: C & F Neck

Type: Formed Wire



### PRODUCT DETAILS

#### General

Application	Double Top Tie
Color Code	Purple
Insulator Throat Neck Type	C & F Neck
Material	Aluminum Clad Steel
Product Category	Ties
Type	Formed Wire

#### Dimensions

Length	17.0 in (431.8 mm)
Weight	0.520 lb (0.24 kg)

#### Conductor Related

Conductor Diameter – Maximum	0.665
Conductor Diameter – Minimum	0.589
Conductor Diameter Range	0.589 – 0.665
Conductor Type	ACSR, AAC, AAAC, Compacted ACSR, Compacted AAC and more

#### Logistics

Pallet Quantity	600
-----------------	-----

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>