



## Non-fitting Straight line Stirrup Clamp Deadend

Catalog ID: 05B3L1A

Non-fitting Straight line Stirrup Clamp Deadend—overhead line connector. It is designed to secure the completeness of conductors as well as protect other electrical line fittings.  
 Conductor compatibility AAC, AAAC, ACAR, ACSR  
 Conductor diameter range 0.18 in – 0.46 in  
 Standard voltage application



### PRODUCT DETAILS

#### General

Bolt Installation Torque (Recommended)	0 ft-lbs
Fitting Type	None
Material	Aluminum
Material – Body	356 T6 Aluminum Alloy
Material – Hardware	Galvanized Steel
Material – Keeper	356 T6 Aluminum Alloy
Number of Pad Holes	0
Product Category	Straight Line
Strength Rating – Ultimate Body	6000 lb (2721.55 kg)
Tension Range	0 lb
Type	Bolted
U-Bolts	2 in (50.8 mm)

#### Dimensions

Clevis Opening	0.75 in (19.05 mm)
Diameter – Bolt	0.375 in (9.53 mm)
Diameter – Pin	0.625 in (15.88 mm)
Weight	1.57 lb (0.71 kg)

#### Logistics

Pallet Quantity	450
-----------------	-----

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
----------------	------------------------------

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>