



## None Fittings Aluminum Straight line Deadend

**Catalog ID: 05B5M0X**

Straight line Deadend—overhead line connector with non-fittings  
 Standard voltage application  
 Conductor diameter range 0.46 in – 0.86 in  
 Conductor Compatibility ACSR;AAC;AAAC  
 Installation with copper and Copper Weld phase conductor



### PRODUCT DETAILS

#### General

Bolt Installation Torque (Recommended)	0 ft-lbs
Fitting Type	None
Material	Ductile Iron; Steel
Material – Body	Ductile Iron
Material – Hardware	Galvanized Steel
Material – Keeper	Ductile Iron
Number of Pad Holes	0
Product Category	Straight Line
Strength Rating – Ultimate Body	10000 lb (4535.92 kg)
Style	Deadend, Straight Line
Tension Range	0 lb
Type	Bolted
U-Bolts	2 in (50.8 mm)

#### Dimensions

Clevis Opening	0.75 in (19.05 mm)
Diameter – Bolt	0.5 in (12.7 mm)
Diameter – Pin	0.625 in (15.88 mm)
Weight	3.72 lb (1.69 kg)

#### Logistics

Pallet Quantity	270
-----------------	-----

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
----------------	------------------------------

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>