



## One-Position Cutout Standoff Bracket

**Catalog ID: 06K1V2Q**

Cutout Standoff Bracket—line construction hardware

It is designed to provide additional strength and support to other power line components and parts.

Bracket used in pole line installation and construction.

Made by 0° 1-Position Cutout / Arrester, three phase medium duty fiberglass.

Distance from pole 36 in



### PRODUCT DETAILS

#### General

Description – End Fitting	1 Position Apparatus Mount
Strength Rating – Minimum Ultimate, Longitudinal (L)	800 lb (362.87 kg)
Strength Rating – Minimum Ultimate, Transverse (T)	5000 lb (2267.96 kg)
Strength Rating – Minimum Ultimate, Vertical (V)	1200 lb (544.31 kg)

#### Dimensions

Diameter – Rod / Tube	1.5 in (38.1 mm)
Distance From Pole	36 in (914.4 mm)
Distance from Pole – Third Phase	13 in (330.2 mm)
Length	36 in (914.4 mm)
Mounting Bolt Spacing	6 in (152.4 mm) 8 in (203.2 mm)
Weight	11.9 lb (5.4 kg)

#### Logistics

Standard Package	5
------------------	---

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>