



Partial Tension Aluminum Compression Splice

Catalog ID: 01C7N8K

Partial Tension Aluminum Compression Splice is one kind of connectors used on overhead line construction and pole line installations. It is a super durable or impermanent association on AAC, ACSR conductors. It is made of Aluminum Alloy against corrosion. Partial tension of 40% tension rating



PRODUCT DETAILS

General

Compression Method	VersaCrimp Tooling ONLYIVC6 (all)
Compression Tool Type	VersaCrimp Tooling ONLYIVC6 (all)
Material	Aluminum Alloy

Dimensions

Length Before Compression	6.0 in (152.4 mm)
Weight	0.294 lb (0.13 kg)

Conductor Related

Conductor Compatibility	ACSR-Sparrow-2-6/1;ACSR-Sparate-2-7/1;ACSR-Robin-1-6/1;ACSR-Raven-1/0-6/1;ACSR-Quail-2/0-6/1;AAC-Iris-2-7;AAC-Pansy-1-7;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAAC 6201 Alloy-Ames-77.47-6/18;AAAC 6201 Alloy-Azusa-123.3-6/18
Conductor Diameter (VersaCrimp) – Maximum	0.447 in (11.35 mm)
Conductor Diameter (VersaCrimp) – Minimum	0.292 in (7.42 mm)

Logistics

Carton Quantity	100
-----------------	-----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>