



## Pisa Anchor Rod Coupling

Catalog ID: 03F6X8Z

Pisa Anchor Rod Coupling–Power Installed Screw Anchor

It is designed to connect two PISA anchor rods to extend the length of the installed anchor.

Hot dipped galvanized per ASTM A153

High tensile strength of 16000 lb



### PRODUCT DETAILS

#### General

|                  |  |
|------------------|--|
| Application      | Helical Anchoring  |
| Coating          | Galvanized, ASTM A-153   |
| Strength Note    | Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength. |
| Tensile Strength | 16000 lb   |
| Type             | Power Installed Screw Anchor (PISA)  |

#### Dimensions

|              |                     |
|--------------|---------------------|
| Rod Diameter | 0.625 in (15.88 mm) |
| Weight       | 0.333 lb (0.15 kg)  |

#### Logistics

|                  |      |
|------------------|------|
| Pallet Quantity  | 4000 |
| Standard Package | 50   |

### RESOURCES AND DOWNLOADS

|                    |                              |
|--------------------|------------------------------|
| Specifications     | <a href="#">Download PDF</a> |
| Technical Drawings | <a href="#">Download PDF</a> |

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>