



## Quadrant Spring Loaded Deadend

**Catalog ID: 05B2W5P**

Quadrant Spring Loaded Deadend—overhead line connector  
 It is designed to secure the completeness of conductors as well as protect other electrical line fittings.  
 Installation with Single 1/2 in U-Bolt  
 Conductor diameter range 0.19 in – 0.48 in



### PRODUCT DETAILS

#### General

Fitting Type	None
Material	Aluminum Alloy; Steel
Material – Body	356 T6 Aluminum Alloy
Material – Hardware	Galvanized Steel
Material – Keeper	356 T6 Aluminum Alloy
Product Category	Quadrant
Strength Rating – Ultimate Body	8000 lb (3628.74 kg)
Type	Bolted
U-Bolts	1 in (25.4 mm)

#### Dimensions

Diameter – Bolt	0.5 in (12.7 mm)
Diameter – Pin	0.625 in (15.88 mm)
Weight	1.18 lb (0.54 kg)

#### Logistics

Pallet Quantity	675
-----------------	-----

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>