



Round Rod Anchor Lead

Catalog ID: 03C0F1G

Round Rod Anchor Lead—ground anchoring products

Used in weak soil conditions

Moderate holding capacities

The anchor lead section has to be install in the proper depth into the soil to meet the power and utility needs in the power line hardwarfe systems.

Galvanized, ASTM A-153

2 Helices

High Tensile Strength of 70000 lb



PRODUCT DETAILS

General

Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Number of Helices	2
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	70000 lb
Torque Rating	2300 ft-lbs
Type	Round Rod Anchors

Dimensions

Anchor Helix Diameter(s)	8 in (203.2 mm) – 10 in (254 mm)
Length	84.000 in (2133.6 mm)
Weight	48.020 lb (21.78 kg)

Logistics

Pallet Quantity	20
Standard Package	1

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>