



Secondary Spacer with Three Conductor

Catalog ID: 05F6L4E

Secondary Spacer is a pre-designed electrical dispersion framework intended for high dependability.

It is easy to install without using any extra tools.

The material of it is composite for its strength, light weight, corrosion resistance, design flexibility and durability features.

Served with with three conductor



PRODUCT DETAILS

General

Color Code	Black
EU RoHS Indicator	No
Material	Composite
Product Category	Spacers

Dimensions

Weight	0.274 lb (0.12 kg)
--------	--------------------

Conductor Related

Conductor Diameter (Covered) – Maximum	0.523 in (13.28 mm)
Conductor Diameter (Covered) – Minimum	0.257 in (6.53 mm)
Conductor Diameter (Covered) Range	0.523 in -0.257 in
Conductor Diameter – Maximum	0.52 in (13.21 mm)
Conductor Diameter – Minimum	0.26 in (6.6 mm)
Conductor Diameter Range	0.26 in – 0.52 in
Conductor Spacing	12 in (304.8 mm)

Logistics

Pallet Quantity	600
-----------------	-----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>