



## Singel Hole Aluminum Compression Terminal

**Catalog ID: 01B2I1N**

Singel Hole Aluminum Compression Terminal is one kind of connectors used on overhead line construction and pole line installations.

All the package, color is customized by our clients.

It is made of Aluminum. Aluminum has lower density than other metals.

It forms a protective layer of oxide to protect the terminal when it exposes to the air.

Aluminum Alloy – Tin Plated with 1 pad hole and 1 spade hole



### PRODUCT DETAILS

#### General

Material	Aluminum Alloy – Tin Plated
Material – Body	Aluminum
Number of Pad Holes	1
Number of Spade Holes	1
Physical Attribute – Number of Holes	1
Plating Type	Tin
Style	Impact Extruded

#### Dimensions

Bolt Diameter	0.38
Diameter – Pad Bolt	0.38 in (9.65 mm)
Dimension – Bolt Hole Size inch	0.380 in (9.65 mm)
Weight	0.098 lb (0.04 kg)

#### Conductor Related

Conductor Compatibility	ACSR-Robin-1-6/1;ACSR-Raven-1/0-6/1;AAC-Pansy-1-7;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAAC 6201 Alloy-Azusa-123.3-6/18
Conductor Diameter (Die Type Tooling) – Maximum	0.419 in (10.64 mm)
Conductor Diameter (Die Type Tooling) – Minimum	0.414 in (10.52 mm)
Conductor Diameter (VersaCrimp) – Maximum	0.419 in (10.64 mm)
Conductor Diameter (VersaCrimp) – Minimum	0.328 in (8.33 mm)
Lug Conductor Type	AL CU

#### Certifications and Compliance

---

UL Listed	Yes
-----------	-----

---

## **RESOURCES AND DOWNLOADS**

---

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

---

*For further technical assistance, please contact us*

### **TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: [sales@ttfpower.com](mailto:sales@ttfpower.com)

Website: <https://ttfpower.com>