



Single Hole Copper Compression Terminal

Catalog ID: 01B1F0P

Single Hole Copper Compression Terminal is one kind of connectors used on overhead line construction and pole line installations. All the package, color is customized by our clients. It is made of Copper with 1 Spade Hole and 1 Pad Hole. Copper with high thermal and electrical conductivity
UL Listed



PRODUCT DETAILS

General

Material	Copper
Material – Body	Copper Rod
Number of Pad Holes	1
Number of Spade Holes	1
Physical Attribute – Number of Holes	1
Plating Type	Tin
Style	Impact Extruded

Dimensions

Bolt Diameter	0.38
Diameter – Pad Bolt	0.38 in (9.65 mm)
Weight	0.294 lb (0.13 kg)

Conductor Related

Conductor Diameter (Die Type Tooling) – Maximum	0.63 in (16 mm)
Conductor Diameter (Die Type Tooling) – Minimum	0.629 in (15.98 mm)
Conductor Diameter (VersaCrimp) – Maximum	0.373 in (9.47 mm)
Conductor Diameter (VersaCrimp) – Minimum	0.414 in (10.52 mm)
Lug Conductor Type	CU

Certifications and Compliance

UL Listed	Yes
-----------	-----

RESOURCES AND DOWNLOADS

Specifications	Download PDF
----------------	------------------------------

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>