



Sprial Vibration Damper

Catalog ID: 05F9L6D

Sprial Vibration Damper is used to absorb vibration emanating from machinery, pedestrian traffic, etc.

It primarily reduce the noise associated with such vibration and procure a more comfortable environment.

Industry standard IEEE 664-1993 and IEEE 1591.2

Used with 0.327 in- 0.461 in cable O.D.



PRODUCT DETAILS

General

Application	Spiral vibration damper
Material	PVC
Product Category	Communications Connectors

Dimensions

Length	51 in (1295.4 mm)
Weight	0.734 lb (0.33 kg)

Conductor Related

Conductor Diameter – Maximum	0.461 in (11.71 mm)
Conductor Diameter – Minimum	0.327 in (8.31 mm)
Conductor Diameter Range	0.327 in – 0.461 in
Conductor Type	ADSS, OPGW and Shield Wire

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>