



Static Wire Compression Deadend

Catalog ID: 05B9X1B

Static Wire Compression Deadend is a type of overhead line connector. It is designed to secure the completeness of conductors as well as protect other electrical line fittings.
 Conductor diameter range 0.306 in – 0.312 in
 Full Tension for alumoweld conductor
 Material of body is forged steel
 Designed with 2-hole pad



PRODUCT DETAILS

General

Bolt Installation Torque (Recommended)	0 ft-lbs
Compression Method	Single Die
Material	Steel
Material – Body	Galvanized Forged Steel
Material – Hardware	Aluminum Alloy
Material – Pad	Cast Aluminum
Number of Bolt Holes	2
Number of Pad Holes	0
Press Minimum	60
Product Category	Steel
Style	Static Wire, 2-hole Pad
Tension Range	0 lb
Type	Compression

Dimensions

Length Before Compression	10.6 in (269.24 mm)
Weight	1.8 lb (0.82 kg)

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>