



Straight Compression Terminal

Catalog ID: 01B2D3E

Straight Compression Terminal is one kind of connectors used on overhead line construction and pole line installations.

All the package, color is customized by our clients.

It is made of Aluminum forming a protective layer of oxide on the terminal surface when exposed to air.

Uni-Grip (single die system)

4 Pad holes



PRODUCT DETAILS

General

Compression Method	Uni-Grip (single die system)
Die Size	13CD
Material & Connection Method	Aluminum Compression
Number of Pad Holes	4
Product Category	Compression Jumper Terminal

Dimensions

Length Before Compression	13.4 in (340.36 mm)
Weight	2.636 lb (1.2 kg)
Width – Pad	3 in (76.2 mm)

Electrical Ratings

Voltage Application	EHV; Standard
---------------------	---------------

Conductor Related

Conductor Compatibility	ACSR-Canary-900-54/7;ACSR-Rail-954-45/7;ACSR-Cardinal-954-54/7;ACSR-Ortolan-1033.5-45/7;AAC-Camellia-1000-61;AAC-Bluebell-1033.5-37;AAC-Larkspur-1033.5-61;AAC-Marigold-1113-61
-------------------------	---

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>