



# **Straight Insulator Side Tie**

# Catalog ID: 01A6E6H

Straight Insulator Side Tie is one kind of connectors used on overhead line construction.

It is designed to secure conductors on double-arm construction in the power line hardware systems.

Insulator Throat Neck Type: F Neck

Semi-Conductive covering over Rigid Black PVC-composite material



#### PRODUCT DETAILS

#### General

Color Code	Red
Insulator Throat Neck Type	F Neck
Material	Composite
Material – Cover and Body	Semi-Conductive covering over Rigid Black PVC
Product Category	Ties

#### **Dimensions**

Insulator Throat Diameter - Maximum	3.38 in (85.85 mm)
Insulator Throat Diameter – Minimum	2.75 in (69.85 mm)
Insulator Throat Diameter Range	2.75 - 3.38
Length	25.000 in (635 mm)
Weight	0.372 lb (0.17 kg)

#### **Conductor Related**

Conductor Diameter (Covered) - Maximum	1.125 in (28.58 mm)
Conductor Diameter (Covered) – Minimum	0.92 in (23.37 mm)
Conductor Diameter (Covered) Range	1.125-0.92
Conductor Diameter – Maximum	1.125
Conductor Diameter – Minimum	0.92
Conductor Diameter Range	0.92 - 1.125
Conductor Type	Covered

## RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

## TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com Website: https://ttfpower.com