



Tangent Standoff Bracket

Catalog ID: 06K9X7K

Tangent Standoff Bracket—line construction hardware
 It is designed to provide additional strength and support to other power line components and parts.
 Bracket used in pole line installation and construction.
 Made by single phase extra heavy duty fiberglass.
 Distance from pole 21 in



PRODUCT DETAILS

General

Description – End Fitting	Cable Suspension Clamp
EU RoHS Indicator	No
Strength Rating – Minimum Ultimate, Transverse (T)	10000 lb (4535.92 kg)
Strength Rating – Minimum Ultimate, Vertical (V)	4000 lb (1814.37 kg)

Dimensions

Diameter – Rod / Tube	2 in (50.8 mm)
Distance From Pole	21 in (533.4 mm)
Length	21 in (533.4 mm)
Mounting Bolt Spacing	8 in (203.2 mm)
Weight	13.5 lb (6.12 kg)

Logistics

Pallet Quantity	64
Standard Package	2

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>