



Thimbleye Square Shaft Lead

Catalog ID: 03C1X1G

Thimbleye Square Shaft Lead—ground anchoring products

Used in weak soil conditions

High holding capacities

The anchor lead section has to be install in the proper depth into the soil to meet the power and utility needs in the power line hardwarfe systems.

Thimbleye

Galvanized, ASTM A-153

2 Helices



PRODUCT DETAILS

General

Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Eyenuit Style	Thimbleye
Number of Helices	2
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	70000 lb
Torque Rating	5500 ft-lbs
Type	Lead Sections

Dimensions

Anchor Helix Diameter(s)	8 in (203.2 mm) – 10 in (254 mm)
Length	36.000 in (914.4 mm)

Logistics

Standard Package	1
------------------	---

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>