



## Thimbleye Swamp Anchor

Catalog ID: 03C0M3Z

Thimbleye Swamp Anchor—foundation anchoring  
 It is designed to utilize in specific soil condition—swamps, bogs, and marshes.  
 Assemble to Square Shaft Extension with through bolt  
 Galvanized, ASTM A-153  
 Eye Nut Style: Thimbleye  
 1 Helix



### PRODUCT DETAILS

#### Dimensions

Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Eye Nut Style	Thimbleye
Number of Helices	1
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	70000 lb
Torque Rating	5500 ft-lbs
Type	Lead Sections

#### Dimensions

Anchor Helix Diameter(s)	10 in (254 mm)
Length	96.000 in (2438.4 mm)
Weight	46 lb (20.87 kg)

#### Logistics

Standard Package	1
------------------	---

### RESOURCES AND DOWNLOADS

Specifications	<a href="#">Download PDF</a>
Technical Drawings	<a href="#">Download PDF</a>

*For further technical assistance, please contact us*

**TTF Power Technology Co., Ltd.**

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>