



Three-Phase Vertical Pin Standoff Bracket

Catalog ID: 06K4F7W

Vertical Pin Standoff Bracket—line construction hardware
 It is designed to provide additional strength and support to other power line components and parts.
 Bracket used in pole line installation and construction.
 Made by three phase medium duty fiberglass with 1 in nylon thread.
 Distance from pole 30 in



PRODUCT DETAILS

General

Description – End Fitting	Vertical Pin
Material – Threads	1" Nylon Threads
Strength Rating – Minimum Ultimate, Longitudinal (L)	900 lb (408.23 kg)
Strength Rating – Minimum Ultimate, Transverse (T)	1500 lb (680.39 kg)
Strength Rating – Minimum Ultimate, Vertical (V)	1500 lb (680.39 kg)

Dimensions

Diameter – Rod / Tube	1.5 in (38.1 mm)
Distance From Pole	30 in (762 mm)
Distance from Pole – Third Phase	24 in (609.6 mm)
Length	30 in (762 mm)
Mounting Bolt Spacing	8 in (203.2 mm)
Weight	18.7 lb (8.48 kg)

Logistics

Standard Package	5
------------------	---

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>